

CREE COB LED 专用电源

SHARP LED Part Number	产品型号 Model	产品图片 Product Picture	工作电压 Voltage range	恒流及精度 Output current	效率 Efficiency	功率因数 Power Factor	输出电压 Output voltage	外型尺寸 Contour Size	可否调光 with the dimmer
MT-G-EZW MP-L	TXM08-0302-XX		AC90-260V	450MA±5%	>80%	>0.50	DC=19-24V	58.5*23.5*22.6mm	
MT-G-EZW MP-L	TXM12-0302-XX		AC90-260V	450MA±5%	>80%	>0.50	DC=19-24V	68*21.5*20mm	
MT-G-EZW MP-L	TXM18-0302-XX		AC90-260V	450MA±5%	>80%	>0.50	DC=19-24V	48*29*20mm	
MT-G-EZW MP-L	TXM07-0607-XX		AC90-260V	150MA±5%	>85%	>0.85	DC=60-80V	58.5*23.5*22.6mm	
MT-G-EZW MP-L	TXM16-0302-XX		450MA±5%	450MA±5%	>80%	>0.50	DC=19-24V	ø57*17mm	
MT-G-EZW	TXM10-0207-XX		AC90-240V	200MA±5%	>80%	>0.95	DC=35-45V	55.3*22.4*21.5mm	
CXA2011	TXM19-0700-XX		AC90-240V	400MA±5%	>80%	>0.85	DC=40-50V	68*23.5*24mm	
CXA2011	TXM11-0700-XX		AC90-240V	450MA±5%	>90%	>0.90	DC=35-50V	53*51*24mm	
CXA2011	TXM14-0701-XX		AC90-240V	450MA±5%	>80%	>0.85	DC=35-45V	58*51*26mm	yes
CXA2011	TXM28-0705-XX		AC90-240V	300MA±5%	>80%	>0.80	DC=35-45V	68*27*21mm	yes
CXA2011	TXM33-0700-XX		AC90-240V	450MA±5%	>85%	>0.90	DC=35-45V	ø52*20mm	